# **SPRING BARS TOOLS**



| MSA    | Length | Kg    |
|--------|--------|-------|
| 10.309 | 140 mm | 0.021 |

Tool for fitting and removing spring bars.

- Aluminium anodised red handle Ø 8 mm
- Stainless steel tip and fork.

The fixing of the tips and forks on the handle is secured by 2 stainless steel M2 screws.



# Spare parts:

| MSA      | Item                                 | Kg    |
|----------|--------------------------------------|-------|
| 10.309-A | (1) Tip Ø 0.80 mm, threading M3      | 0.006 |
| 10.309-B | (2) Fork width 1.20 mm, threading M3 | 0.006 |
| 10.309-V | (3) Screw, threading M2              | 0.001 |



| MSA    | Length | Kg    |
|--------|--------|-------|
| 10.313 | 135 mm | 0.034 |

Tool for fitting and removing spring bars.

- Aluminium anodised black handle Ø 8 mm
- Stainless steel reversible tip and fork easily interchangeable due to maintaining chucks.



#### Spare parts:

| MSA      |   | Kg    |
|----------|---|-------|
| 10.302-A | (1) Reversible tip Ø 0.80 and width 1.20 mm | 0.006 |
| 10.302-B | (2) Fork width 4.00 mm                      | 0.006 |



| MSA    | Length | Kg    |
|--------|--------|-------|
| 10.302 | 135 mm | 0.034 |

Tool for fitting and removing spring bars.

- Knurled steel handle Ø 7 mm
- Steel tips easily interchangeable due to maintaining chucks.



#### Spare parts:

| MSA      | Item   | Kg    |
|----------|--|-------|
| 10.302-A | (1) Reversible tip Ø 0.80 mm and width 1.20 mm | 0.004 |
| 10.302-B | (2) Fork width 4.00 mm                         | 0.004 |



(2)

| MSA    | Length | Kg    |
|--------|--------|-------|
| 10.304 | 147 mm | 0.025 |

Tool for fitting and removing spring bars.

- Aluminium hexagonal handle Ø 10 mm with 2 graduated scales in millimetres and inches
- Interchangeable hardened steel tips.
- \* Delivered with tip MSA10.304-A and fork MSA10.304-B


## Spare parts:





(1)

# SPRING BARS TOOLS



| MSA    | Length | Kg    |
|--------|--------|-------|
| 10.301 | 105 mm | 0.007 |

- Tool for fitting and removing spring bars. Knurled aluminium handle  $\varnothing$  6 mm with graduated scale in mm
- Interchangeable steel tips.

## Spare parts:

| MSA      |                          | Kg    |
|----------|--------------------------|-------|
| 10.301-A | <b>(1)</b> Tip Ø 0.70 mm | 0.006 |
| 10.301-B | (2) Fork width 2.00 mm   | 0.006 |



| MSA    | Length | Kg    |
|--------|--------|-------|
| 10.303 | 145 mm | 0.028 |

Tool for fitting and removing spring bars. - Knurled steel handle

- Interchangeable hardened steel tips.
- \* Delivered with tip MSA10.304-A and fork MSA10.304-B



| MSA        |                        | Kg    |
|------------|------------------------|-------|
| 10.304-A * | (1) Tip Ø 0.80 mm      | 0.001 |
| 10.304-B * | (2) Fork width 3.00 mm | 0.001 |
| 10.304-C   | Fork width 1.20 mm     | 0.001 |

