



BACKFIX



Item No. : VH-26.00387

Bracket with one way friction for screwing / unscrewing watch backs...

The new friction wheel developed by VOH makes this bracket an essential tool with any workshop in after-sales service or production. The simple and reliable release system ensures sufficient and regular locking on watertight watchcases.

Factory pre-set torques :	250 cNm
Repeatability:	± 10%
Range of setting:	1.2 – 3.5 Nm
Ø wheel:	160 mm
Distance base-stitch:	80 mm
Distance axis- vertical frame:	44 mm
Adjustment bases:	Slit 12.0 x 5.5 mm / hole Ø 12.0 mm
Key adjustment (Rawlyer):	Slit 10.0 x 3.5 mm / hole Ø 9.0 mm
Key fixation (Rawlyer):	Tie rod M5
Key adjustment (Bergeon):	Slit 8.5 mm / hole Ø 8.0 x 9.0 mm
Key fixation (Bergeon):	with side screw M4

Delivery: With base board in black agglomerate wood 275 x 160 mm

Note: The modification of the friction torque requires the use of adequate tools



BACKFIX SAV



Item No. : VH-25.01083

BACKFIX SAV – screwing and unscrewing watchcase backs with suction cups and ratchet wrench

Tool set to screw/unscrew the watchcase backs on a rack press.

Content of the set:

- 1 x Universal holder for screwing and unscrewing case backs. (VH-26.00880)
- 1 x Ratchet wrench with adapter for suction cups. (VH-25.00902)
- 6 x Red suction cups / 75 shore:
dia 24mm (VH-26.00331), dia 28mm (VH-26.00332), dia 31mm (VH-26.00333),
dia 35mm (VH-26.00334), dia 40mm (VH-26.00318), dia 45mm (VH-26.00335)

